

GEHFI -250

ENGINE

Manufacturer	FPT - Fiat Power Train
Model	NEF67 TE2A
Power	293 hp (1800rpm) 234 hp (1500rpm)
Cylinder	6 in-line
Displacement	--
Compression	--
Aspiration	Turbocharged
Combustion	--
Consumption	45 l/h (1800rpm) 44 l/h (1500rpm)
Cooling System	Radiator and fan
Filters	Air, fuel and oil
DC System	12V cc (with battery included), alternator and charger
Panel	RPM, hour meter, coolant temperature, oil pressure, manual start
Protection	Engine stopped with overheating and low oil pressure



ALTERNATOR

Manufacturer	Heimer
Model	ATED
Type	Synchronous, brushless, 4 poles, 12 leads 3 phase or single phase (optional)
Connection	Star with accessible neutral
Regulation	Electronic voltage regulation within 2%
Cooling System	Shaft mounted fan
Isolation	Class "H"
Bearings	Single or double bearing (available under consult)



POWER

Stand By	250 kVA - 200 KW / 60Hz	200 KVA - 160 KW / 50 Hz
Prime	182 kVA - 145 KW / 60Hz	182 KVA - 145 KW / 50 Hz

DIMENSIONS

Open Set	2500 mm L x 700 mm W x 1600 mm H - 1780 Kg
Silent Set	3600 mm L x 1100 mm W x 1830 mm H - 2080 Kg

Base: steel base MIG welded with rubber feet for engine and alternator support for use during about 8 hours. (May be supplied separately if requested).

Silent Enclosure: (optional) Soundproofed to 75dB at 7m or 85dB at 1.5m

AUTOMATIC SWITCHBOARD

Equipped with microprocessed modules of start and stop control and monitoring of engine protection variables.



DPC 560



DKG 307



RGK-60



DS-5520



DS-5510



DS-5560



EGCP-2

Accessories included: Muffler, flexible connection and vibra-stops. Technical, operation and maintenance manuals, electrical diagrams.

* Pictures for illustrations only.

